

Job Name:	
Submitted By:	



Submittal Sheet For:	UT024GLSILSFHG / YN024GLSI24RPG
----------------------	--

Date _____

Ref. _____

Floor-Ceiling Mount Ductless 24SEER Inverter Heat Pump

System Full Set Model: **UYT024GLSI24RL**

AHRI Reference Number: **217048767**

Cooling Mode Performance

Rated Cooling	22,200 BTU/hr
Ambient Range	5°F ~ 131°F
SEER Rating	20.0 BTU/W·h
EER Rating	11.7 BTU/W·h

* 100% Capacity @ Indoor DB 80°F/WB 67°F


Heating Mode Performance

Rated Heating	24,400 BTU/hr
Ambient Range	-13°F ~ 86°F
HSPF2 IV (V)	9.5 (8.5) BTU/W·h
COP	3.0 (W/W)

*High Heat (47°F) = 24,400 BTU / Low Heat (17°F) = 14,400 BTU / COP (5°F) = 2.0



Floor-Ceiling Mount Ductless Indoor Unit



Outdoor Condensing Unit



Installation Kit (Pipe + Cable)



Handheld Remote Controller

Electrical Information

Rated Input (W)	Cooling	Heating
	2,200	2,320
Rated Current (A)	11.4	11.9
Breaker Needed	25A (Double-Pole)	
Power Supply	208~230V, 1Ph, 60Hz	

Piping and Refrigerant

Liquid Line (OD)	1/4"
Suction Line (OD)	5/8"
Refrigerant Precharge	R454b (Selectable Lineset)
Max Length/Height Diff.	65 ft. / 50 ft.

This combination is
Energy-Star certified.






Interior Unit (Air Handler) Specifications

Type	Heat Pump
Sound Level (dBA)	53 (Turbo)/52 (Hi)/48 (Med)/44 (Lo)/40 (Mute)
Auto Air Circulation	2-Way Louver (Up-Down + Left-Right)
Dimensions (WDH)	41"-1/2 x 26"-1/2 x 9"-1/4
Weight (lbs)	57.3


Exterior Unit (Condenser) Specifications

Sound Level (dBA)	54
Recommended Room Size	750~1,000 Sq. ft.
Minimum Room Size (Sq. ft.)	62 (Ceiling Suspended)/260 (Floor/Low Wall)
Compressor	Inverter-Driven Rotary
Dimensions (WDH)	38"-1/2 x 16"-5/8 x 31"-5/8
Weight (lbs)	104.7






Underside View



Front View



Side View

Model	A	B	C	D	E	F	G	H
YN024GLSI24RPG	910 mm	803 mm	359 mm	607 mm	421 mm	390 mm	60 mm	63 mm
	35-7/8"	31-5/8"	14-1/8"	23-7/8"	16-5/8"	15-3/8"	2-3/8"	2-1/2"

Warranty Information and Length



Complete warranty details are available with the vendor or online at <https://www.pdhvac.com/support/warranty/>. This high-quality system is eligible for up to a 5-year limited warranty on the compressor, and 5 years on other internal parts. To qualify for this warranty, the system must be installed within 90 days and registered properly. All other installations that are unregistered qualify for only 1-year parts/compressor warranty.

Outstanding Features

- LED Display
- Energy Saving
- Ultra-Thin Design
- Dual Drain Options
- Customizable Timer
- Eco-Friendly Refrigerant
- Whisper-Quiet Operation
- Power Loss Memory Recovery

Available Accessories

Part Number	Description
IKT-LCVR4P-KIT	<i>Decorative PVC Line Cover Kit</i>
IKT-LNBR-1/4-3/8	<i>BendAid Flexible Easy Bender Kit</i>
BRK-FRM-C-2P	<i>Folding Mounting Bracket w/ Leveler</i>
IKT-UVL32UL-AG	<i>UVC Bacterial Disinfection Kit</i>
IKT-SURPRK-DV2	<i>Ultimate Surge and Power Protection</i>