

Job Name:	
Submitted By:	



Submittal Sheet For:	WT024GLSI25HLH / YN024GLSI25RPH
----------------------	--

Date _____

Ref. _____

Wall-Mounted Ductless 25SEER Inverter Heat Pump

System Full Set Model: **WYT024GLSI25RH**

AHRI Reference Number: **217048757**

Cooling Mode Performance

Rated Cooling	24,000 BTU/hr
Ambient Range	5°F ~ 131°F
SEER Rating	23 BTU/W·h
EER Rating	12 BTU/W·h

* 100% Capacity @ Indoor DB 80°F/WB 67°F

Heating Mode Performance

Rated Heating	24,000 BTU/hr
Ambient Range	-22°F ~ 86°F
HSPF2 IV (V)	10.0 (9.0) BTU/W·h
COP	3.5 (W/W)

* High Heat (47°F) = 24,000 BTU / Low Heat (17°F) = 15,500 BTU / COP (5°F) = 1.8



Wall-Mounted Indoor Unit



Outdoor Condensing Unit



Installation Kit (Pipe + Cable)



Handheld Remote Controller

Electrical Information

	Cooling	Heating
Rated Input (W)	1,860	2,000
Rated Current (A)	8.3	9.0
Breaker Needed	30A (Double-Pole)	
Power Supply	208~230V, 1Ph, 60Hz	

Piping and Refrigerant

Liquid Line (OD)	1/4"
Suction Line (OD)	5/8"
Refrigerant Precharge	R454b (Selectable Lineset)
Max Length/Height Diff.	65 ft. / 50 ft.

This combination is
Energy-Star certified.





Interior Unit (Air Handler) Specifications

Type	Heat Pump
Sound Level (dBA)	49 (Turbo) / 47 (Hi) / 42 (Med) / 37 (Lo) / 32 (Mute)
Auto Air Circulation	2-Way Louver (Up-Down + Left-Right)
Dimensions (WDH)	43"-1/8 x 8"-3/4 x 13"-1/8
Weight (lbs)	30.9


Exterior Unit (Condenser) Specifications


Sound Level (dBA)	61
Recommended Room Size	750~1,000 Sq. ft.
Minimum Room Size	63 Sq. ft.
Compressor	Inverter-Driven Rotary
Dimensions (WDH)	38"-1/2 x 16"-5/8 x 31"-5/8
Weight (lbs)	108

WT024GLSI25HLH Air Handler Dimensional Data



Model	A	B	C
WT024GLSI25HLH	1096 mm	222.3 mm	334 mm
	43-1/8"	8-3/4"	13-1/8"





Model	D	E	F	G	H	I	J	K
YN024GLSI25RPH	910 mm	804 mm	353 mm	607 mm	421 mm	390 mm	63 mm	54 mm
	35-7/8"	31-5/8"	13-7/8"	23-7/8"	16-5/8"	15-3/8"	2-1/2"	2-1/8"

Warranty Information and Length



Complete warranty details are available with the vendor or online at <https://www.pdhvac.com/support/warranty/>. This high-quality system is eligible for up to a 5-year limited warranty on the compressor, and 5 years on other internal parts. To qualify for this warranty, the system must be installed within 90 days and registered properly. All other installations that are unregistered qualify for only 1-year parts/compressor warranty.

Outstanding Features

- LED Display
- Energy Saving
- Ultra-Thin Design
- Dual Drain Options
- Customizable Timer
- Eco-Friendly Refrigerant
- Whisper-Quiet Operation
- Power Loss Memory Recovery

Available Accessories

Part Number	Description
IKT-LCVR4P-KIT	<i>Decorative PVC Line Cover Kit</i>
IKT-LNBR-1/4-3/8	<i>BendAid Flexible Easy Bender Kit</i>
BRK-FRM-C-2P	<i>Folding Mounting Bracket w/ Leveler</i>
IKT-UVL32UL-AG	<i>UVC Bacterial Disinfection Kit</i>
IKT-SURPRK-DV2	<i>Ultimate Surge and Power Protection</i>