



## GA Series SPECIFICATIONS

### Heavy Duty Commercial Air Curtains Two, Three, Four and Five Foot Lengths (Each with: Low, Medium and High Velocity Versions)



#### STANDARD FEATURES

- DESIGNED FOR STANDARD WALL HUNG INSTALLATION
- LATEST DESIGN ATTRACTIVE APPEARANCE
- ULTRA QUIET DESIGN WITH HIGH PERFORMANCE
- ADJUSTABLE DISCHARGE LOUVER FOR DIRECTING THE AIR FLOW
- AVAILABLE IN 2, 3, 4 AND 5 FOOT LENGTHS
- SIMPLE PUSH BUTTON OPERATION
- 2 SPEED PSC FAN MOTOR
- ULTRA QUIET CROSS FLOW BLOWER WHEELS
- AVAILABLE WITH 4", 5" AND 6" DIAMETER BLOWERS FOR OPTIMUM VERSATILITY
- EXTRA HEAVY GAUGE GALVANIZED STEEL CABINET
- ELECTROSTATIC POWDER COAT PAINT
- LOUVERED ABS PLASTIC RETURN AIR PANELS WITH COORDINATED COLOR
- FULL SIZE HANGING BRACKET

#### OPTIONAL FEATURES: WIRELESS REMOTE CONTROLLER

Model No.	Length (Foot)	Blower Wheel Dia.	Air Velocity	Rated Voltage	Rated Frequency	Max Input Power (Watt)	Heater Power (Watt)	Air Speed (Ft/sec)	Std. Mounting Height	Average Sound (db)	Weight (Lbs)	Dimensions (In)
GA-90ALU2	2'	4"	Low	110 / 120	60Hz	55	-	23	6'	60	24	24 x 7 x 7
GA-125ALU2	2'	5"	Medium	110 / 120	60Hz	90	-	26	8'	60	31	24 x 8.5 x 7.5
GA-150ALU2	2'	6"	High	110 / 1220	60Hz	110	-	30	10'	60	38	24 x 10.5 x 10.5
GA-90ALU3	3'	4"	Low	110 / 120	60Hz	60	-	23	6'	64	29	36 x 7 x 7
GA-125ALU3	3'	5"	Medium	110 / 120	60Hz	110	-	26	8'	64	44	36 x 8.5 x 7.5
GA-150ALU3	3'	6"	High	110 / 120	60Hz	130	-	30	10'	64	55	36 x 10.5 x 10.5
GA-90ALU4	4'	4"	Low	110 / 120	60Hz	80	-	23	6'	67	36	48 x 7 x 7
GA-125ALU4	4'	5"	Medium	110 / 120	60Hz	120	-	26	8'	67	53	48 x 8.5 x 7.5
GA-150ALU4	4'	6"	High	110 / 120	60Hz	150	-	30	10'	67	67	48 x 10.5 x 10.5
GA-90ALU5	5'	4"	Low	110 / 120	60Hz	100	-	23	6'	67	42	60 x 7 x 7
GA-125ALU5	5'	5"	Medium	110 / 120	60Hz	140	-	26	8'	67	60	60 x 8.5 x 7.5
GA-150ALU5	5'	6"	High	110 / 120	60Hz	180	-	30	10'	67	77	60 x 10.5 x 10.5